

RECIPROCATING
SAWS

SPECIFICATIONS	DC305K	DCS380L1	DCS380B	DCS385L
Volts	36V	20V MAX*	20V MAX*	18V
Stroke/Min	0-3,000 spm	0-3,000 spm	0-3,000 spm	0-3,000 spm
Stroke Length	1-1/8"	1-1/8"	1-1/8"	1-1/8"
Keyless Blade Clamp	Yes, 4-position	Yes	Yes	Yes
Adjustable Shoe	Yes	Yes	Yes	Yes
Electric Brake	Yes	Yes	Yes	Yes
Weight	8.4 lbs	7.35 lbs	5.93 lbs (tool only)	7.25 lbs
Charger/Batteries	1 Hour Charger / (1) 36V	Fast Charger / (1) 20V MAX* Lithium Ion 3.0 Ah	Sold Separately	1 Hour Charger / (1) 18V XRP™ Li-Ion



SPECIFICATIONS	DC385K	DC385B
Volts	18V	18V
Keyless Blade Clamp	Yes	Yes
Stroke/Min	0-3,000 spm	0-3,000 spm
Stroke Length	1-1/8"	1-1/8"
Electric Brake	Yes	Yes
Weight	8.2 lbs	5.8 lbs (tool only)
Charger/Batteries	1 Hour Charger / (1) 18V XRP™	Sold Separately

DCS380L1

4-Position
Blade Clamp

Allows for flush cutting and increased positional versatility with tool-free blade changes

1-1/8" (28.6mm)
Stroke Length
Delivers a fast cutting speed

CONCRETE
VIBRATOR

SPECIFICATIONS	DC530KA	DC530B
Volts	18V	18V
Vibrator Diameter	1-1/8"	1-1/8"
Shaft Length	4'	4'
Vibrations per Minute	14,000 vpm	14,000 vpm
Weight	9.3 lbs	7.05 lbs (tool only)
Charger/Batteries	1 Hour Charger / (2) 18V XRP™	Sold Separately
Includes	-	-